

# Hi-Flo™ Gas Solenoid Valves & Piloted Manifolds



Solenoid Solutions offers a wide array of solenoid valves and piloted manifold arrangements specifically for natural and liquid propane gas applications requiring from 10,000 up to 550,000 BTUs.



The high flow, **Hi-Flo™**, series of gas solenoid valves are designed for **high BTU appliances, outdoor grills and barbecues, decorative fire bowls, propane heaters, fire pits, gas lighting and gas torch applications.**



[SolenoidSolutionsInc.com](http://SolenoidSolutionsInc.com)  
888.825.8405 • 814.838.3190

## Hi-Flo Gas Series of Valves Include:

- Hi-Flo - a 7 Series solenoid valve to the 150,000 BTUs
- Hi-Flo+ - a 7 Series solenoid valve to the 300,000 BTUs
- Hi-Flo Magnum - a 7 Series solenoid valve to the 550,000 BTUs

Many of our manifold designs include simple low power pilot valve and one or more Hi-Flo Valves to deliver the precise gas flow.

## Other Gas Solenoid Valves:

NC, NO, Directional, Axial, Proportional

## Specifications:

Valve Series	Operation	Body Size	Port Sizes	Orifice	Max BTU
Wattmizer	Axial Flow	1"	#10-32 to 1/8"	.025" to 1/8" (body .025" to 5/64" (Stop)	25,000
7 Series		1-3/16"	1/8 "to 1/4"		50,000
7 Series Hi-Flo			1/4 "to 3/8"	3/8"	150,000
7 Series Hi-Flo+			1/2"	3/8"	300,000
7 Series Hi-Flo Magnum			3/8 "to 3/4"	3/4"	550,000



SolenoidSolutionsInc.com  
888.825.8405 • 814.838.3190